



## **LINE//** Specification

### GN-1330 E

	Working height*	5,80 m
A	Platform height	3,80 m
	Platform dimension (length x width)	
C D	- platform retracted	1,35 m x 70 cm
B D	- platform extended	1,95 m x 70 cm
E	Height - stowed	1,97 m
F	Height- rails folded (Available from 08.2019)	1,68 m
G	Height – transport position (minimum height)	1,14 m
H	Length - stowed	1,42 m
K	Width	0,76 m
I / J	Ground clearance (center/with pothole guards deployed)	6,5/2 cm

### Productivity

	Max platform occupancy (Indoor/outdoor)	2/0 Indoor only
	Lift capacity	240 kg
	Drive speed - stowed	3,2 km/h
	Drive speed - raised	0,5 km/h
	Gradeability**	25%
	Turning radius - inside	0,4 m
	Turning radius - outside	1,35 m
	Raised / lower speed	30-33/25-30 sec
	Controls	proportional
	Tyres – solid non-marking	23 cm x 8 cm

### Power

	Power source	24V DC (2 AGM maintenance free batteries) 12V 110 Ah
	Hydraulic system capacity	5 L

### Sound and Vibration levels

	Sound pressure level - ground	<70 dBA
	Sound Pressure level - platform	<70 dBA
	Vibration	<2,5 m/s <sup>2</sup>

### Weight\*\*\*

		880 kg
--	--	--------

### CE – Standard Compliance

EC Directives: 2006/42/EC – machinery EN280:2013; Directives 2004/108/EC (EMC); Directives 2006/95/EC (LVD)

\* the metric equivalent of working height adds 2m to platform height.

\*\* gradeability applies on driving on slopes. See operator's manual for details regarding slope ratings

\*\*\* weight will vary depending on options and/or country standards

